


Always use correct Personal Protective Equipment


# 62C ACCELERATOR

### Description



62C Accelerator is an additive for two pack paint systems. Addition of up to 5% by volume of 62C Accelerator to 2 pack paint systems will approximately halve curing and pot life times.

### Products



**Product Type:** Aliphatic Polyisocyanate Resin  
**Colour:** Clear  
**Density:** 0.870 kg/L

### Properties



**VOC:** 871 g/L  
**Volume Solids:** 0.05%

### Directions For Use



**Mixing Ratio:** Add up to 5% 62C Accelerator (by volume) to the two pack paint system.

### Health & Safety



For detailed information refer to Safety Data Sheet (SDS). Contains Isocyanates, avoid contact with skin and eyes.  
 Avoid breathing vapour. Use protective clothing and respiratory equipment. Product is flammable.

### Transport & Storage



**Sizes:** 250 ml, 1 lt  
**Dangerous Goods:** 3A  
**UN:** 1263  
**Hazchem:** 3[Y]E  
**Packing Group:** II  
**Shipment name:** PAINT Related Material (flammable)  
**Flash point:** 4°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.